





mats Noise Protection	name / specification	PRICE	
		1 sheet / 1 package	1 m <sup>2</sup>
	<p><b>Vibrofiltr 1.5</b></p> <p>thickness: 1,5 mm (± 0,1 mm)  size of sheet: 0.5m x 0.7m / 0,35 m<sup>2</sup>  mechanical loss coefficient at 200 Hz: 0,25  quantity in the package: 25 sheets / 8,75 m<sup>2</sup>  weight of 1 m<sup>2</sup>, not less: 2,5 kg</p>	<p>1 sheet: <b>00,00</b></p> <p>1 package: <b>000,00</b></p>	00,00
	<p><b>Vibrofiltr 2.0</b></p> <p>thickness: 2,0 mm (± 0,1 mm)  size of sheet: 0.5m x 0.7m / 0,35 m<sup>2</sup>  mechanical loss coefficient at 200 Hz: 0,38  quantity in the package: 20 sheets / 7 m<sup>2</sup>  weight of 1 m<sup>2</sup>, not less: 3,0 kg</p>	<p>1 sheet: <b>00,00</b></p> <p>1 package: <b>000,00</b></p>	00,00
	<p><b>Vibrofiltr 3.0</b></p> <p>thickness: 3,0 mm (± 0,2 mm)  size of sheet: 0.5m x 0.7m / 0,35 m<sup>2</sup>  mechanical loss coefficient at 200 Hz: 0,50  quantity in the package: 15 sheets / 5,25 m<sup>2</sup>  weight of 1 m<sup>2</sup>, not less: 4,5 kg</p>	<p>1 sheet: <b>00,00</b></p> <p>1 package: <b>000,00</b></p>	00,00
	<p><b>Vibrofiltr 4.0</b></p> <p>thickness: 4,0 mm (± 0,2 mm)  size of sheet: 0.5m x 0.7m / 0,35 m<sup>2</sup>  mechanical loss coefficient at 200 Hz: 0,60  quantity in the package: 10 sheets / 3,5 m<sup>2</sup>  weight of 1 m<sup>2</sup>, not less: 6,4 kg</p>	<p>1 sheet: <b>00,00</b></p> <p>1 package: <b>000,00</b></p>	000,00
<ul style="list-style-type: none"> <li>• material: composite on the basis of high-quality butyl rubber and polymers reinforced with an embossed aluminum foil with a seal</li> <li>• thickness of aluminum foil: 0.1 mm (100 μm)</li> <li>• operating temperature range: -50°C to +160°C</li> <li>• strength of binding of butyl material to the surface of aluminum foil, not less than: 6 N / cm<sup>2</sup></li> <li>• stability of a viscous polymer layer with a temperature of + 90°C for 24 hours: detachment and creep are unacceptable</li> <li>• antivibration product that absorbs vibrations, self-adhesive, non-toxic, odorless, non-flammable (self-extinguishing), waterproof and oils with anticorrosive and sealing properties, does not contain bitumen additives (without tar and asphalt)</li> </ul>			